



(slika je simbolična)

Predfilter»FUTURA«Kov. pos.0.3 µm, Vel. 4, G 1, Avt.

Kategorija: [Pre-filter with metal bowl and sight glass](#)Šifra: **156571RIE**

Kratek opis

Pre-filter »FUTURA« with metal container and viewing tube, 0.3 µm, Size 4, G 1, 1.5 - 16 bar, Temp. -10°C to 50°C, Fully-automatic

Pre-filters in modern design for compliance with strict compressed air purity requirements.

Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Impregnated paper At $P_2 = 6$ bar and pressure drop $\Delta p = 0.02$ bar
Merjenje pretoka	G 1
Navoj	Fully-automatic
Odtok kondenzata	PA66 GF60
Ohišje	Metal container with viewing tube
Posoda	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	0.3
Rang filtra [µm]	1.5
Min. vhodni tlak [bar]	4
Velikost	16
Max. vhodni tlak [bar]	50
Max. temperaturno območje [°C]	63.0
C [mm]	85.0
A [mm]	269.0
B [mm]	1500
Pretok [l/min]	