



## 2/2-el.mag.vent.,NC,vod. krm., 24V DC,8W,FKM,G3/8,0.1-10bar

Kategorija: [Solenoid valve, NC, pilot-operated](#)  
Šifra: **102930RIE**

(slika je simbolična)

### Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 24V DC, 8W, Medium temp. -10°C to 140°C, FKM, G 3/8, PN 0.1 - 10bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 3/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	FPM
Min. obratovalni tlak [bar]	0.1
Vrsta	3
Max. obratovalni tlak [bar]	10
DN	12
B [mm]	50.0
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	140