

Datum: 01.07.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

## **2/2-el.mag.vent.,NC,vod. krm., 24V DC,8W,NBR,G3/4,0.2-16bar**

Kategorija: [Solenoid valve, NC, pilot-operated](#)  
Šifra: **102942RIE**

(slika je simbolična)

### **Kratek opis**

2/2-way solenoid valve brass, NC, pilot operated, 24V DC, 8W, Medium temp. -10°C to 90°C, NBR, G 3/4, PN 0.2 - 16bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### **Tehnične Specifikacije**

|                              |  |
|------------------------------|--|
| Min. sobna temperatura [°C]  | -10  |
| Min. temperatura medija [°C] | -10  |
| Električni priključek        | For connector socket<br>Pg 9/Pg 11 acc. to<br>ISO 4400 |
| Ffunkcija                    | normally closed (NC)                                   |
| IP zaščita                   | IP 65 (with connector<br>socket fitted)                |
| Navoj                        | G 3/4  |
| Notranji deli                | Stainless steel  |
| Ohišje                       | Brass  |
| Sedež ventila                | Brass  |
| Tesnilo                      | NBR  |
| Min. obratovalni tlak [bar]  | 0.2  |
| Vrsta                        | 6  |
| Max. obratovalni tlak [bar]  | 16   |
| DN                           | 19   |
| A [mm]                       | 54.0   |
| Max. sobna temperatura [°C]  | 80   |
| Max. temperatura medija [°C] | 90   |
| B [mm]                       | 104.0  |