

Datum: 19.04.2026

2/2-el.mag.vent.,NO,vod. krm., 230-240V,NBR,G3/4,0.2-16bar

Kategorija: [Solenoid valve, NO, pilot-operated](#)
Šifra: **102949RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NO, pilot operated, 230-240V, 50-60Hz, 16VA, Medium temp. -10°C to 90°C, NBR, G 3/4, PN 0.2 - 16bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally open (NO)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 3/4
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.2
Vrsta	6
Max. obratovalni tlak [bar]	16
DN	19
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	90
B [mm]	104.0