



## 2/2-el.mag.vent.,NO,vod. krm.,24V DC,NBR,G1,PN0.2-16bar

Kategorija: [Solenoid valve, NO, pilot-operated](#)  
Šifra: **102957RIE**

(slika je simbolična)

### Kratek opis

2/2-way solenoid valve brass, NO, pilot operated, 24 V DC, Medium temperature -10 °C to 90 °C, G 1, PN 0.2 - 16 bar Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally open (NO)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.2
Vrsta	6
Max. obratovalni tlak [bar]	16
DN	25
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	90
B [mm]	104.0