

Datum: 02.06.2026

**2/2-el.magn.ventil,NC,direkt.krm.,230-240V,50-60Hz,G1/4,0-5bar**Kategorija: [Solenoid valve, NC, directly operated](#)
Šifra: **102889RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NC, dir. operated, 230 - 240V,
50 - 60Hz, 16VA, Medium temp. -10°C to 140°C, FPM, G 1/4,
PN 0 - 5bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or
low-viscosity, neutral media.

Tehnične Specifikacije

| | |
|---------------------------------|--|
| Min. sobna temperatura [°C] | -10 |
| Min. temperatura medija [°C] | -10 |
| Električni priključek | For connector socket Pg 9/Pg 11 acc. to ISO 4400 |
| Ffunkcija | normally closed (NC) |
| IP zaščita | IP 65 (with connector socket fitted) |
| Navoj | G 1/4 |
| Notranji deli | Stainless steel |
| Ohišje | Brass |
| Sedež ventila | Brass |
| Tesnilo | FPM |
| Vrsta | 2 |
| DN | 4.5 |
| Max. obratovalni tlak [bar] | 5 |
| B [mm] | 40.0 |
| A [mm] | 54.0 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 140 |