

Datum: 18.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

[2/2-el.magn.ventil,NC,direkt.krm.,,230V,50Hz,FPM,G1/8,PN0-18bar](#)

Kategorija: [Solenoid valve, NC, directly operated](#)
Šifra: **102883RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NC, directly operated, 230V, 50Hz, 10VA, Medium temp. -10°C to 140°C, FPM, G 1/8, PN 0 - 18bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	FPM
Vrsta	1
DN	2.3
Max. obratovalni tlak [bar]	18
B [mm]	30.0
A [mm]	41.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	140