

Datum: 01.07.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

## 2/2-el.magn.ventil,NC,direkt.krm.,24V DC,8W,FKM,G1/4,PN0-6bar

Kategorija: [Solenoid valve, NC, directly operated](#)  
Šifra: **102894RIE**

(slika je simbolična)

### Kratek opis

2/2-way solenoid valve brass, NC, directly operated, 24V DC, 8W, Medium temp. -10°C to 140°C, FKM, G 1/4, PN 0 - 6bar  
Economy series available in three different versions  
- Directly operated  
- Combined operation  
- Pilot-operated  
For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/4
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	FPM
Vrsta	2
DN	3
Max. obratovalni tlak [bar]	6
B [mm]	40.0
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	140