

Datum: 01.07.2026

[2/2-el.magn.ventil,NC,direkt.krm.,24V DC,8W,FKM,G1/8,PN0-9bar](#)

Kategorija: [Solenoid valve, NC, directly operated](#)
Šifra: **102891RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NC, directly operated, 24V DC, 8W, Medium temp. -10°C to 140°C, FKM, G 1/8, PN 0 - 9bar
Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	FPM
Vrsta	2
DN	2.5
Max. obratovalni tlak [bar]	9
B [mm]	40.0
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	140