

Datum: 08.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



2/2-potni el.mag. ventil,AISI 304,FPM,NC, op.,24 V DC,G 1/2

Kategorija: [Solenoid valve, NC, combined operation](#)
Šifra: **102981RIE**

(slika je simbolična)

Kratek opis

2/2-way sol. valve,AISI 304,FPM,NC,force pilot op., 24 V DC,med. temperature -15°C - 100°C,amb.temp.-15°C - 75°C,G 1/2,PN 0-3 bar
Available versions
- Directly operated
- Combined operation

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Električni priključek	For Pg 11P connector socket acc. to DIN 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	G 1/2
Notranji deli	Stainless steel
Ohišje	Stainless steel 1.4301
Sedež ventila	Stainless steel 1.4301
Tesnilo	FPM
Max. obratovalni tlak [bar]	3
Vrsta	3
DN	16
B [mm]	71.0
Max. sobna temperatura [°C]	75
A [mm]	80.0
Max. temperatura medija [°C]	100