



(slika je simbolična)

[2/2-potni el.mag. ventil, NC, prisil. vod. krm., 230 V, 1 1/4](#)

Kategorija: [Solenoid valve, NC, combined operation](#)
Šifra: **102841RIE**

Kratek opis

2/2-way solenoid valve brass, NC, force pilot operated, 230 V, 50-60 Hz, Rp 1 1/4, NBR, Medium temp. -20 °C to 85 °C, PN 0 - 9 bar
Standard series, proven over many years, available in three different versions
- Directly operated
- Combined operation
- Pilot-operated
For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

| | |
|------------------------------|-------------------------------------|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Električni priključek | ISO 4400; cable socket (Pg 11P) |
| Ffunkcija | normally closed (NC) |
| IP zaščita | IP65 (with connector socket fitted) |
| Navoj | Rp 1 1/4 |
| Notranji deli | Stainless steel |
| Ohišje | Brass |
| Sedež ventila | Brass |
| Standardni navoj | Rp thread acc. to ISO 7-1 |
| Tesnilo | NBR |
| Vrsta | 3 |
| Max. obratovalni tlak [bar] | 9 |
| DN | 28 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 85 |
| A [mm] | 86.0 |
| B [mm] | 95.0 |