



## [2/2-potni el.mag. ventil, NC, prisil. vod. krm., 230 V, 3/4](#)

Kategorija: [Solenoid valve, NC, combined operation](#)  
Šifra: **102838RIE**

(slika je simbolična)

### Kratek opis

2/2-way solenoid valve brass, NC, force pilot operated, 230 V, 50-60 Hz, Rp 3/4, FKM, Medium temp. -20 °C to 120 °C, PN 0 - 9 bar

Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Električni priključek	ISO 4400; cable socket (Pg 11P)
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	Rp 3/4
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	FKM
Vrsta	3
Max. obratovalni tlak [bar]	9
DN	19
Max. sobna temperatura [°C]	50
B [mm]	73.0
A [mm]	80.0
Max. temperatura medija [°C]	120