

Datum: 02.07.2026



2/2-potni el.mag. ventil, NC, vod. krm., 24 V DC, 1

Kategorija: [Solenoid valve, NC, pilot-operated](#)
Šifra: **102874RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 24 V DC, Medium temperature -20 °C to 120 °C, Rp 1, PN 0.35 - 9 bar Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

| | |
|------------------------------|-------------------------------------|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Električni priključek | ISO 4400; cable socket (Pg 11P) |
| Ffunkcija | normally closed (NC) |
| IP zaščita | IP65 (with connector socket fitted) |
| Navoj | Rp 1 |
| Notranji deli | Stainless steel |
| Ohišje | Brass |
| Sedež ventila | Brass |
| Standardni navoj | Rp thread acc. to ISO 7-1 |
| Tesnilo | FKM |
| Min. obratovalni tlak [bar] | 0.35 |
| Vrsta | 4 |
| Max. obratovalni tlak [bar] | 9 |
| DN | 25 |
| Max. sobna temperatura [°C] | 50 |
| A [mm] | 80.0 |
| B [mm] | 95.0 |
| Max. temperatura medija [°C] | 120 |