

Datum: 01.07.2026



(slika je simbolična)

## 2/2-potni el.mag. ventil, NC, vod. krm., 24 V DC, 3/4

Kategorija: [Solenoid valve, NC, pilot-operated](#)  
Šifra: **102871RIE**

### Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 24 V DC, Medium temperature -20 °C to 85 °C, Rp 3/4, PN 0.35 - 7 bar Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Električni priključek	ISO 4400; cable socket (Pg 11P)
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	Rp 3/4
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.35
Vrsta	3
Max. obratovalni tlak [bar]	7
DN	19
Max. sobna temperatura [°C]	50
B [mm]	71.0
A [mm]	80.0
Max. temperatura medija [°C]	85