

Datum: 17.03.2026



(slika je simbolična)

2/2-potni el.mag. ventil NC, vod. krm., 24 V DC, G 1

Kategorija: [Solenoid valve, NC, pilot-operated, 24 V DC](#)Šifra: **116562RIE**

Kratek opis

2/2-way solenoid valve, Stainless steel, NC, pilot operated, 24 V DC, Medium temp. max. 80 °C / 90 °C, G 1, PN 0.5 - 10 bar

Standard series available in two different versions:

-Directly operated

-Pilot-operated

Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Tehnične Specifikacije

IP zaščita	IP 65
Navoj	G 1
Notranji deli	Stainless steel
Ohišje	Stainless steel 1.4301
Sedež ventila	Stainless steel 1.4301
Standardni navoj	G thread acc. to DIN EN
Tesnilo	ISO 228-1
Min. obratovalni tlak [bar]	FPM
Vrsta	0.5
Max. obratovalni tlak [bar]	3
DN	10
A [mm]	25
B [mm]	70.0
C [mm]	92.0
	124.0