

Datum: 28.06.2026



(slika je simbolična)

## 2/2-potni el.mag. ventil NO, direk. upr., 230 V, 50 Hz

Kategorija: [Solenoid valve, NO, 230 V, 50 Hz, high pressures](#)  
Šifra: **116591RIE**

### Kratek opis

2/2-way solenoid valve, Brass, NO, directly operated, 230 V, 50 Hz, Medium temp. max. 80 °C / 90 °C, G 1/8, PN 0 - 20 bar

Standard series available in two different versions:

-Directly operated

-Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4.

Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4.

Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

### Tehnične Specifikacije

IP zaščita	IP 65
Navoj	G 1/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	FPM
DN	1.5
Vrsta	2
Max. obratovalni tlak [bar]	20
B [mm]	40.0
A [mm]	70.0
C [mm]	76.0