

Datum: 05.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



2/2-potni el.mag. ventil NO, direk. upr., 24 V DC

Kategorija: [Solenoid valve, NO, 24 V DC, standard type](#)
Šifra: **116549RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve, Brass, NO, directly operated, 24 V DC, Medium temperature max. 80 °C / 90 °C, G 1/2, PN 0 - 7 bar

Standard series available in two different versions:

-Directly operated

-Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4.

Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4.

Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Tehnične Specifikacije

IP zaščita	IP 65
Navoj	G 1/2
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	FPM
Vrsta	2
DN	5
Max. obratovalni tlak [bar]	7
B [mm]	52.0
A [mm]	85.0
C [mm]	92.0