

**Datum:** 03.07.2025



## 2/2-potni el.mag. ventil NO, vod. krm., 24 V DC, G 3/4

Kategorija: [Solenoid valve, NO, pilot-operated, 24 V DC](#)  
Šifra: **116571RIE**

(slika je simbolična)

### Kratek opis

2/2-way solenoid valve, Brass, NO, pilot operated, 24 V DC, Medium temperature max. 80 °C / 90 °C, G 3/4, PN 0.5 - 7 bar

Standard series available in two different versions:

- Directly operated
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4.

Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4.

Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

### Tehnične Specifikacije

|                             |                                   |
|-----------------------------|-----------------------------------|
| IP zaščita                  | IP 65                             |
| Navoj                       | G 3/4                             |
| Notranji deli               | Stainless steel                   |
| Ohišje                      | Brass                             |
| Sedež ventila               | Brass                             |
| Standardni navoj            | G thread acc. to DIN EN ISO 228-1 |
| Tesnilo                     | FPM                               |
| Min. obratovalni tlak [bar] | 0.5                               |
| Vrsta                       | 4                                 |
| Max. obratovalni tlak [bar] | 7                                 |
| DN                          | 20                                |
| A [mm]                      | 70.0                              |
| B [mm]                      | 82.0                              |
| C [mm]                      | 120.8                             |