



(slika je simbolična)

2/2-potni el.mag. ventil NO, vod. krm., 230 V, 50 Hz

Kategorija: [Solenoid valve, NO, pilot-operated, 230 V, 50 Hz](#)
Šifra: **116568RIE**

Kratek opis

2/2-way solenoid valve, Stainless steel, NO, pilot operated, 230 V, 50 Hz, Medium temp. max. 80°C/90°C, G 1, PN 0.5 - 7 bar

Standard series available in two different versions:

-Directly operated

-Pilot-operated

Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Tehnične Specifikacije

| | |
|-----------------------------|-------------------------|
| IP zaščita | IP 65 |
| Navoj | G 1 |
| Notranji deli | Stainless steel |
| Ohišje | Stainless steel 1.4301 |
| Sedež ventila | Stainless steel 1.4301 |
| Standardni navoj | G thread acc. to DIN EN |
| Tesnilo | ISO 228-1 |
| Min. obratovalni tlak [bar] | FPM |
| Vrsta | 0.5 |
| Max. obratovalni tlak [bar] | 4 |
| DN | 7 |
| A [mm] | 25 |
| B [mm] | 70.0 |
| C [mm] | 92.0 |
| | 129.3 |