

Datum: 09.03.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



2/2-potni el.mag.vent.AISI 304,FPM,NC,direkt.krm.24V,NPT1/8

Kategorija: [Solenoid valve, NC, directly operated](#)
Šifra: **102974RIE**

(slika je simbolična)

Kratek opis

2/2-way sol. valve,AISI 304,FPM,NC,directly op.,24 V
DC,med. temp. -15 °C - 120 °C,amb.temp.-15°C - 55°C,NPT
1/8, PN 0-14 bar
Available versions
- Directly operated
- Combined operation

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -15 |
| Min. temperatura medija [°C] | -15 |
| Električni priključek | For Pg 11P connector socket acc. to DIN 4400 |
| Ffunkcija | normally closed (NC) |
| IP zaščita | IP65 (with connector socket fitted) |
| Navoj | NPT 1/8 |
| Notranji deli | Stainless steel |
| Ohišje | Stainless steel 1.4301 |
| Sedež ventila | Stainless steel 1.4301 |
| Tesnilo | FPM |
| Vrsta | 1 |
| DN | 2.4 |
| Max. obratovalni tlak [bar] | 14 |
| B [mm] | 30.0 |
| Max. sobna temperatura [°C] | 55 |
| A [mm] | 91.0 |
| Max. temperatura medija [°C] | 120 |