

Datum: 13.06.2026

## 2/2 solenoid valve, NC, G1, PN 0-12, FPM, comb. opera., 110V AC

Kategorija: [Solenoid valve, normally closed, combined operation, AC](#)  
Šifra: **129424RIE**

(slika je simbolična)

### Kratek opis

2/2-way solenoid valve, NC, Brass, G1, DN25, PN 0-12, FPM, combined operated, 110V AC, Med.temp -15 to 100, Ambi.temp -10 to 50

In many areas, such as plant engineering, process technology or filling technology, solenoid valves are an optimum solution for control and regulation of fluids. With this professional standard series, RIEGLER offers fluid valves designed in Germany and produced in Europe. A consistently managed modular system guarantees a broad spectrum of possible valve forms in regards to sealing materials or valve bodies. If you cannot find your required specification in our standard products, please contact us.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	Connector socket, industrial standard type A - EN 175301-803-A normally closed (NC) IP65 (with connector socket fitted)
Ffunkcija	
IP zaščita	
Navoj	G 1
Notranji deli	Brass and stainless steel
Ohišje	Brass
Sedež ventila	Brass and stainless steel
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	FPM
Max. obratovalni tlak [bar]	12
DN	25
Max. sobna temperatura [°C]	50
C [mm]	70.0
A [mm]	95.0
Max. temperatura medija [°C]	100
Napetost	110V AC
B [mm]	139.0