TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 15.11.2026



(slika je simbolična)

2/2 solenoid valve, NC, G114, PN 0.5-12, FPM, pilot-opera. 24V AC

Kategorija: Solenoid valve, normally closed, pilot-operated, AC
Šifra: **129514RIE**

Kratek opis

2/2-way solenoid valve, NC, Brass, G114, DN32, PN 0.5-12, FPM, pilot-operated, 24V AC, Med.temp -15 to 100, Ambi.temp -10 to 50
In many areas, such as plant engineering, process technology or filling technology, solenoid valves are an optimum solution for control and regulation of fluids. With this professional standard series, RIEGLER offers fluid valves designed in Germany and produced in Europe. A consistently managed modular system guarantees a broad spectrum of possible valve forms in regards to sealing materials or valve bodies. If you cannot find your required specification in our standard products, please contact us.

Tehnične Specifikacije

Min. temperatura medija [°C]	-15
Min. sobna temperatura [°C]	-10
Električni priključek	Connector socket, industrial standard type A – EN 175301-803-A
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	G 1 1/4
Notranji deli	Brass and stainless steel
Ohišje	Brass
Sedež ventila	Brass and stainless steel
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	FPM
Min. obratovalni tlak [bar]	0.5
Max. obratovalni tlak [bar]	12
Napetost	24V AC
DN	32
Max. sobna temperatura [°C]	50
C [mm]	96.0
Max. temperatura medija [°C]	100
A [mm]	132.0
B [mm]	145.0