**TRG d.o.o.**
**Celovška cesta 150, 1000 Ljubljana**

**Davčna št.:** SI 56119488
**Telefon:** 01 500 14 42
**E-mail:** info@podjetje-trg.si
**WWW:** www.www.karcher-trg.si

**Datum:** 28.11.2026



(slika je simbolična)

# 2/2 solenoid valve, NC, G12, PN 0.5-16, NBR, pilot-opera., 12V DC

Kategorija: Solenoid valve, normally closed, pilot-operated, DC
Šifra: **129560RIE**

## Kratek opis

2/2-way solenoid valve, NC, Brass, G12, DN13, PN 0.5-16, NBR, pilot-operated, 12V DC, Med.temp -20 to 85, Ambi.temp -10 to 50
In many areas, such as plant engineering, process technology or filling technology, solenoid valves are an optimum solution for control and regulation of fluids. With this professional standard series, RIEGLER offers fluid valves designed in Germany and produced in Europe. A consistently managed modular system guarantees a broad spectrum of possible valve forms in regards to sealing materials or valve bodies. If you cannot find your required specification in our standard products, please contact us.

## Tehnične Specifikacije

| | |
|---|---|
| Min. temperatura medija [°C] | -20 |
| Min. sobna temperatura [°C] | -10 |
| Električni priključek | Connector socket, industrial standard type A – EN 175301-803-A |
| Ffunkcija | normally closed (NC) |
| IP zaščita | IP65 (with connector socket fitted) |
| Navoj | G 1/2 |
| Notranji deli | Brass and stainless steel |
| Ohišje | Brass |
| Sedež ventila | Brass and stainless steel |
| Standardni navoj | G thread acc. to DIN EN ISO 228-1 |
| Tesnilo | NBR |
| Min. obratovalni tlak [bar] | 0.5 |
| Napetost | 12V DC |
| DN | 13 |
| Max. obratovalni tlak [bar] | 16 |
| C [mm] | 48.0 |
| Max. sobna temperatura [°C] | 50 |
| A [mm] | 67.0 |
| Max. temperatura medija [°C] | 85 |
| B [mm] | 103.0 |