

2/2 solenoid valve, NC, G14, PN 0-10, FPM, direc. opera. 230V AC

Kategorija: [Solenoid valve, normally closed, directly operated, AC](#)
Šifra: **129296RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve, NC, Brass, G14, DN4.0, PN 0-10, FPM, directly operated 230V AC, Med.temp -15 to 100, Ambi.temp -20 to 55

In many areas, such as plant engineering, process technology or filling technology, solenoid valves are an optimum solution for control and regulation of fluids. With this professional standard series, RIEGLER offers fluid valves designed in Germany and produced in Europe. A consistently managed modular system guarantees a broad spectrum of possible valve forms in regards to sealing materials or valve bodies. If you cannot find your required specification in our standard products, please contact us.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -15 |
| Električni priključek | Connector socket acc. to DIN EN 175301-803 standard type A normally closed (NC) IP 65 (bei Verwendung der Gerätesteckdose) |
| Ffunkcija | G 1/4 |
| IP zaščita | Brass and stainless steel |
| Navoj | Brass |
| Notranji deli | Brass and stainless steel |
| Ohišje | G thread acc. to DIN EN ISO 228-1 |
| Sedež ventila | FPM |
| Standardni navoj | 4 |
| Tesnilo | 10 |
| DN | 29.5 |
| Max. obratovalni tlak [bar] | 50.0 |
| C [mm] | 55 |
| A [mm] | 80.0 |
| Max. sobna temperatura [°C] | 100 |
| B [mm] | 230V AC |
| Max. temperatura medija [°C] | |
| Napetost | |