

Datum: 12.06.2026

2/2 solenoid valve, NC, G14, PN 0-10, NBR, direc. opera. 24V AC

Kategorija: [Solenoid valve, normally closed, directly operated, AC](#)
Šifra: **129306RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve, NC, Brass, G14, DN4.0, PN 0-10, NBR, directly operated 24V AC, Med.temp -20 to 85, Ambi.temp -20 to 55

In many areas, such as plant engineering, process technology or filling technology, solenoid valves are an optimum solution for control and regulation of fluids. With this professional standard series, RIEGLER offers fluid valves designed in Germany and produced in Europe. A consistently managed modular system guarantees a broad spectrum of possible valve forms in regards to sealing materials or valve bodies. If you cannot find your required specification in our standard products, please contact us.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Električni priključek	Connector socket acc. to DIN EN 175301-803 standard type A normally closed (NC) IP 65 (bei Verwendung der Gerätesteckdose)
Ffunkcija	G 1/4
IP zaščita	Brass and stainless steel
Navoj	Brass
Notranji deli	Brass and stainless steel
Ohišje	G thread acc. to DIN EN ISO 228-1
Sedež ventila	NBR
Standardni navoj	4
Tesnilo	Max. obratovalni tlak [bar]
DN	10
Max. obratovalni tlak [bar]	Napetost
Max. obratovalni tlak [bar]	24V AC
Max. obratovalni tlak [bar]	C [mm]
Max. obratovalni tlak [bar]	29.5
Max. obratovalni tlak [bar]	A [mm]
Max. obratovalni tlak [bar]	50.0
Max. sobna temperatura [°C]	Max. sobna temperatura [°C]
Max. sobna temperatura [°C]	55
Max. sobna temperatura [°C]	B [mm]
Max. sobna temperatura [°C]	80.0
Max. sobna temperatura [°C]	Max. temperatura medija [°C]
Max. sobna temperatura [°C]	85