

Datum: 13.06.2026

2/2 solenoid valve NO, G112, PN 0.5-10, NBR, pilot-opera. 230V AC

Kategorija: [Solenoid valve, normally open, pilot-operated, AC](#)
Šifra: **129606RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve, NO, Brass, G112, DN40, PN 0.5-10, NBR, pilot-operated, 230V AC, Med.temp -20 to 85, Ambi.temp -10 to 50

In many areas, such as plant engineering, process technology or filling technology, solenoid valves are an optimum solution for control and regulation of fluids. With this professional standard series, RIEGLER offers fluid valves designed in Germany and produced in Europe. A consistently managed modular system guarantees a broad spectrum of possible valve forms in regards to sealing materials or valve bodies. If you cannot find your required specification in our standard products, please contact us.

Tehnične Specifikacije

Min. temperatura medija [°C]	-20
Min. sobna temperatura [°C]	-10
Električni priključek	Connector socket, industrial standard type A - EN 175301-803-A normally open (NO) IP65 (with connector socket fitted)
Ffunkcija	G 1 1/2
IP zaščita	Brass and stainless steel
Navoj	Brass
Notranji deli	Brass and stainless steel
Ohišje	G thread acc. to DIN EN ISO 228-1
Sedež ventila	NBR
Standardni navoj	0.5
Tesnilo	10
Min. obratovalni tlak [bar]	40
Max. obratovalni tlak [bar]	50
DN	85
Max. sobna temperatura [°C]	96.0
Max. temperatura medija [°C]	132.0
C [mm]	145.0
A [mm]	230V AC
B [mm]	
Napetost	