

Datum: 05.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## 3-pot. krog. ventil, L-izpust, ner.jeklo 1.4408, G 1, DN 25

Kategorija: [3-way ball valve, L-bore](#)  
Šifra: **103467RIE**

### Kratek opis

3-way ball valve, L-hole, Stainless steel 1.4408, Operating temperature max. 160 °C, G 1, DN 25, PN max. 63 bar  
With L or T-bore, reduced bore.  
Version for sealing on all sides with integrated ISO flange plate (ISO 5211).  
The lever can be turned 360° to allow several switching variants.

### Tehnične Specifikacije

Material	Stainless steel 1.4408
Navoj	G 1
Ročica	Stainless steel
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	RTFE
C Ø [mm]	20.0
DN	25
Max. obratovalni tlak [bar]	63
B [mm]	83.0
L [mm]	100.0
A [mm]	133.0
Max. delovna temperatura [°C]	160