

Datum: 04.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[3-pot. krog. ventil, L-izpust, nikljana med., 1 1/4, DN 32](#)

Kategorija: [3-way ball valve, sealing on all sides, L-bore](#)
Šifra: **103388RIE**

Kratek opis

3-way ball valve, L-hole, nickel-plated brass, Medium / ambient temp. -15 °C to 100 °C, Rp 1 1/4, DN 32, PN max. 16 bar
The medium can enter via any of the ports to allow several switching variants.
3-way ball valves for diverting media.

Tehnične Specifikacije

| | |
|--|---------------------------|
| Min. sobna temperatura [°C] | -15 |
| Min. temperatura medija [°C] | -15 |
| Indikator položaja | Galvanised steel |
| Krogla | Bright brass |
| Material navojev | Bright brass |
| Navoj | Rp 1 1/4 |
| Ohišje | Nickel-plated brass |
| Ročica | Aluminium, painted black |
| Standardni navoj | Rp thread acc. to ISO 7-1 |
| Tesnilo | PTFE / FKM |
| Vzmet | Stainless steel |
| Max. obratovalni tlak pri 20 ° C [bar] | 16 |
| Bore inball | 29 |
| DN | 32 |
| E [mm] | 34.0 |
| C Ø [mm] | 67.0 |
| Max. sobna temperatura [°C] | 100 |
| Max. temperatura medija [°C] | 100 |
| B [mm] | 121.0 |
| L [mm] | 130.0 |
| A [mm] | 195.0 |