

Datum: 02.07.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

## **3-pot. krog. ventil, T-izpust, ner.jeklo 1.4408, G11/2, DN40**

Kategorija: [553](#)  
Šifra: **135934RIE**

(slika je simbolična)

### **Kratek opis**

3-way ball valve, T-hole, Stainless steel 1.4408, G 1 1/2, DN 40, Operating temperature -20 °C to 180 °C, PN max. 63 bar With L or T-bore, reduced bore.

Version for sealing on all sides with integrated ISO flange plate (ISO 5211).

The lever can be turned 360° to allow several switching variants.

### **Tehnične Specifikacije**

|                                |  |
|--------------------------------|--|
| Min. delovna temperatura [°C]  | -20  |
| Bore diameter padlock ISO 5211 | ca. 7.9<br>F 07                              |
| Krogelno tesnilo               | RTFE (15 % glass fibre reinforced PTFE)      |
| Krogla                         | Stainless steel 1.4401                       |
| Navoj                          | G 1 1/2                                      |
| Ohišje                         | Stainless steel 1.4408                       |
| Ročica                         | Stainless steel 1.4301, with plastic coating |
| Standardni navoj               | G thread acc. to DIN EN ISO 228-1            |
| Stebelno tesnilo               | RTFE (15 % glass fibre reinforced PTFE)      |
| H2 [mm]                        | 14.3   |
| C Ø [mm]                       | 32.0   |
| DN                             | 40   |
| Delovni tlak                   | 63 bar (dependent on temperature)            |
| H1 [mm]                        | 78.3   |
| B [mm]                         | 120.3  |
| L [mm]                         | 125.8  |
| Max. delovna temperatura [°C]  | 180  |
| A [mm]                         | 197.5  |