

Datum: 30.03.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

3-pot. krog. ventil, T-izpust, ner.jeklo 1.4408, G3/8, DN 10

Kategorija: [553](#)
Šifra: **135929RIE**

(slika je simbolična)

Kratek opis

3-way ball valve, T-hole, Stainless steel 1.4408, G 3/8, DN 10, Operating temperature -20 °C to 180 °C, PN max. 63 bar
With L or T-bore, reduced bore.

Version for sealing on all sides with integrated ISO flange plate (ISO 5211).

The lever can be turned 360° to allow several switching variants.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Bore diameter padlock ISO 5211 | ca. 7.9 F 04 |
| Krogelno tesnilo | RTFE (15 % glass fibre reinforced PTFE) |
| Krogla | Stainless steel 1.4401 |
| Navoj | G 3/8 |
| Ohišje | Stainless steel 1.4408 |
| Ročica | Stainless steel 1.4301, with plastic coating |
| Standardni navoj | G thread acc. to DIN EN ISO 228-1 |
| Stebelno tesnilo | RTFE (15 % glass fibre reinforced PTFE) |
| H2 [mm] | 9.0 |
| DN | 10 |
| C Ø [mm] | 11.0 |
| H1 [mm] | 38.2 |
| Delovni tlak | 63 bar (dependent on temperature) |
| L [mm] | 75.7 |
| B [mm] | 77.5 |
| A [mm] | 112.0 |
| Max. delovna temperatura [°C] | 180 |