

Datum: 03.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

3-potni krogelni ventil, L-izpust, nikljana medenina, Rp 1, DN 25

Kategorija: [3-way ball valve, sealing on all sides, L-bore](#)
Šifra: **103387RIE**

Kratek opis

3-way ball valve, L-hole, nickel-plated brass, Medium / ambient temp. -15 °C to 100 °C, Rp 1, DN 25, PN max. 25 bar

The medium can enter via any of the ports to allow several switching variants.

3-way ball valves for diverting media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Indikator položaja	Galvanised steel
Krogla	Bright brass
Material navojev	Bright brass
Navoj	Rp 1
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	PTFE / FKM
Vzmet	Stainless steel
Bore inball	23
DN	25
Max. obratovalni tlak pri 20 ° C [bar]	25
E [mm]	31.0
C Ø [mm]	58.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
B [mm]	102.0
L [mm]	113.0
A [mm]	160.0