

Datum: 25.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## 3-potni krogelni ventil, nikljana medenina, L-izpust, Rp 1/2

Kategorija: [3-way ball valve, lower media connection, L-bore](#)  
Šifra: **136328RIE**

### Kratek opis

3-way ball valve, nickel-plated brass, Connection bottom, L-hole, Rp 1/2, DN 15, Operating temp. -15 °C to 120 °C, PN max. 25 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Nickel-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 1/2
Ohišje	Nickel-plated brass (CW617N)
Ročica	Steel with plastic coating
Standardni navoj	Rp thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / FKM
DN	15
E [mm]	15.0
PN [bar]	25
a/f [mm]	27
H1 [mm]	31.0
H2 [mm]	33.5
B [mm]	62.0
L [mm]	64.0
A [mm]	115.0
Max. delovna temperatura [°C]	120