



(slika je simbolična)

[3-potni krogelni ventil, nikljana medenina, L-izpust, Rp 1/4](#)

Kategorija: [3-way ball valve, lower media connection, L-bore](#)
Šifra: **136326RIE**

Kratek opis

3-way ball valve, nickel-plated brass, Connection bottom, L-hole, Rp 1/4, DN 8, Operating temp. -15 °C to 120 °C, PN max. 25 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Nickel-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 1/4
Ohišje	Nickel-plated brass (CW617N)
Ročica	Steel with plastic coating
Standardni navoj	Rp thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / FKM
DN	8
E [mm]	11.0
a/f [mm]	22
PN [bar]	25
H2 [mm]	26.0
H1 [mm]	28.5
L [mm]	52.0
B [mm]	60.0
A [mm]	115.0
Max. delovna temperatura [°C]	120