

Datum: 26.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

3-potni krogelni ventil, nikljana medenina, L-izpust, Rp 3/4

Kategorija: [3-way ball valve, lower media connection, L-bore](#)
Šifra: **136329RIE**

Kratek opis

3-way ball valve, nickel-plated brass, Connection bottom, L-hole, Rp 3/4, DN 20, Operating temp. -15 °C to 120 °C, PN max. 16 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

Tehnične Specifikacije

| | |
|-------------------------------|------------------------------|
| Min. delovna temperatura [°C] | -15 |
| Krogelno tesnilo | PTFE |
| Krogla | Nickel-plated brass (CW617N) |
| Material navojev | Brass |
| Navoj | Rp 3/4 |
| Ohišje | Nickel-plated brass (CW617N) |
| Ročica | Steel with plastic coating |
| Standardni navoj | Rp thread acc. to ISO 7-1 |
| Stebelno tesnilo | PTFE / FKM |
| PN [bar] | 16 |
| E [mm] | 16.3 |
| DN | 20 |
| a/f [mm] | 32 |
| H2 [mm] | 39.5 |
| H1 [mm] | 42.0 |
| B [mm] | 43.0 |
| L [mm] | 74.0 |
| A [mm] | 115.0 |
| Max. delovna temperatura [°C] | 120 |