

Datum: 25.06.2026



(slika je simbolična)

## **3-potni krogelni ventil, nikljana medenina, L-izpust, Rp 3/8**

Kategorija: [3-way ball valve, lower media connection, L-bore](#)  
Šifra: **136327RIE**

### **Kratek opis**

3-way ball valve, nickel-plated brass, Connection bottom, L-hole, Rp 3/8, DN 10, Operating temp. -15 °C to 120 °C, PN max. 25 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

### **Tehnične Specifikacije**

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Nickel-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 3/8
Ohišje	Nickel-plated brass (CW617N)
Ročica	Steel with plastic coating
Standardni navoj	Rp thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / FKM
DN	10
E [mm]	11.4
a/f [mm]	22
PN [bar]	25
H2 [mm]	26.0
H1 [mm]	28.5
L [mm]	52.0
B [mm]	60.0
A [mm]	115.0
Max. delovna temperatura [°C]	120