

Datum: 26.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

3-potni krogelni ventil, nikljana medenina, T-izpust, Rp 1/2

Kategorija: [3-way ball valve, lower media connection, T-bore](#)
Šifra: **136336RIE**

Kratek opis

3-way ball valve, nickel-plated brass, Connection bottom, T-hole, Rp 1/2, DN 15, Operating temp. -15 °C to 120 °C, PN max. 25 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Nickel-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 1/2
Ohišje	Nickel-plated brass (CW617N)
Ročica	Steel with plastic coating
Standardni navoj	Rp thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / FKM
DN	15
E [mm]	15.0
PN [bar]	25
a/f [mm]	27
H1 [mm]	31.0
H2 [mm]	33.5
B [mm]	62.0
L [mm]	64.0
A [mm]	115.0
Max. delovna temperatura [°C]	120