

Datum: 26.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## [3-potni krogelni ventil, nikljana medenina, T-izpust, Rp 1/4](#)

Kategorija: [3-way ball valve, lower media connection, T-bore](#)  
Šifra: **136334RIE**

### Kratek opis

3-way ball valve, nickel-plated brass, Connection bottom, T-hole, Rp 1/4, DN 8, Operating temp. -15 °C to 120 °C, PN max. 25 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Nickel-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 1/4
Ohišje	Nickel-plated brass (CW617N)
Ročica	Steel with plastic coating
Standardni navoj	Rp thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / FKM
DN	8
E [mm]	11.0
a/f [mm]	22
PN [bar]	25
H2 [mm]	26.0
H1 [mm]	28.5
L [mm]	52.0
B [mm]	60.0
A [mm]	115.0
Max. delovna temperatura [°C]	120