

Datum: 10.05.2026



(slika je simbolična)

## 3-potni krogelni ventil, T-izpust, lahka izvedba, Rp 1/2

Kategorija: [3-way ball valves, standard type, T-bore](#)  
Šifra: **103369RIE**

### Kratek opis

3-way ball valve, T-hole, standard type, nickel-plated brass, Medium/ambient temp. -15 °C to 100 °C, Rp 1/2, PN max. 40 bar  
Sealing on all sides with T-bore.  
The lever of this model can only be turned 90° rather than 360°.  
Only two valve positions are therefore possible instead of four.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Krogla	Nickel-plated brass
Material navojev	Nickel-plated brass
Navoj	Rp 1/2
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	PTFE
Vzmet	Stainless steel
Bore inball	13
DN	15
E [mm]	21.0
C Ø [mm]	38.0
Max. obratovalni tlak pri 20 °C [bar]	40
L [mm]	80.0
B [mm]	85.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
A [mm]	130.0