

Datum: 10.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## 3-potni krogelni ventil, T-izpust, lahka izvedba, Rp 1

Kategorija: [3-way ball valves, standard type, T-bore](#)  
Šifra: **103371RIE**

### Kratek opis

3-way ball valve, T-hole, standard type, nickel-plated brass, Medium/ambient temp. -15 °C to 100 °C, Rp 1, PN max. 25 bar

Sealing on all sides with T-bore.

The lever of this model can only be turned 90° rather than 360°.

Only two valve positions are therefore possible instead of four.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Krogla	Nickel-plated brass
Material navojev	Nickel-plated brass
Navoj	Rp 1
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	PTFE
Vzmet	Stainless steel
Bore inball	23
DN	25
Max. obratovalni tlak pri 20 ° C [bar]	25
E [mm]	31.0
C Ø [mm]	58.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
B [mm]	102.0
L [mm]	113.0
A [mm]	160.0