

Datum: 28.05.2026

(slika je simbolična)

3-potni med. krog. ventil, Pneuma. vklop, L-izpust, 1 1/2

Kategorija: [Brass ball valve, single-acting actuator, L-bore](#)
Šifra: **103557RIE**

Kratek opis

3-way brass ball valve, Pneumat. actuation drive, L-hole,
Operating temperature -20°C to 70°C, Rp 1 1/2, DN 40, PN
max. 25 bar
3-way cock, L-bore or T-bore, full bore.
Pneumatic actuators, double- or single acting version and
integrated end-position feedback.

Tehnične Specifikacije

| | |
|-----------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Adapter ventila | Supplied as standard |
| Material krogelnega ventila | Nickel-plated brass, with ISO flange plate |
| Navoj | Rp 1 1/2 |
| Pogonski material | Anodised aluminium |
| Položaj | L 2 |
| Premaz za krogelni ventil | PTFE / FKM |
| Premaz za pogon | NBR |
| Različica | single-acting |
| Priporočeni vodeni tlak [bar] | 5.5 |
| Max. vodeni tlak aktuatorja [bar] | 10 |
| PN [bar] | 25 |
| DN | 40 |
| D [mm] | 43.0 |
| a/f [mm] | 55 |
| Max. delovna temperatura [°C] | 70 |
| Kot vrtenja [°] | 90 |
| L [mm] | 135.0 |
| A [mm] | 180.0 |
| B [mm] | 193.5 |