

Datum: 20.04.2026



3-potni med. krog. ventil, Pneuma. vklop, T-izpust, 1 1/4

Kategorija: [Brass ball valve, double-acting actuator, T-bore](#)
Šifra: **103561RIE**

(slika je simbolična)

Kratek opis

3-way brass ball valve, Pneumat. actuation drive, T-hole,
Operating temperature -20°C to 70°C, Rp 1 1/4, DN 32, PN
max. 40 bar
3-way cock, L-bore or T-bore, full bore.
Pneumatic actuators, double- or single acting version and
integrated end-position feedback.

Tehnične Specifikacije

| | |
|-----------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Adapter ventila | Supplied as standard |
| Material krogelnega ventila | Nickel-plated brass, with ISO flange plate |
| Navoj | Rp 1 1/4 |
| Pogonski material | Anodised aluminium |
| Položaj | T 3 |
| Premaz za krogelni ventil | PTFE / FKM |
| Premaz za pogon | NBR |
| Različica | double-acting |
| Max. vodeni tlak [bar] | 5.5 |
| Priporočeni vodeni tlak [bar] | 5.5 |
| Max. vodeni tlak aktuatorja [bar] | 10 |
| DN | 32 |
| D [mm] | 37.0 |
| PN [bar] | 40 |
| a/f [mm] | 55 |
| Max. delovna temperatura [°C] | 70 |
| Kot vrtenja [°] | 90 |
| L [mm] | 118.0 |
| A [mm] | 161.0 |
| B [mm] | 191.5 |