

Datum: 20.04.2026



3-potni med. krog. ventil, Pneumat. vklop, T-izpust, 3/4

Kategorija: [Brass ball valve, double-acting actuator, T-bore](#)
Šifra: **103559RIE**

(slika je simbolična)

Kratek opis

3-way brass ball valve, Pneumat. actuation drive, T-hole,
Operating temperature -20 °C to 70 °C, Rp 3/4, DN 20, PN
max. 40 bar
3-way cock, L-bore or T-bore, full bore.
Pneumatic actuators, double- or single acting version and
integrated end-position feedback.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 3/4
Pogonski material	Anodised aluminium
Položaj	T 3
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Max. vodeni tlak [bar]	5.5
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
DN	20
D [mm]	24.0
a/f [mm]	31
PN [bar]	40
Max. delovna temperatura [°C]	70
L [mm]	76.0
Kot vrtenja [°]	90
A [mm]	133.0
B [mm]	146.0