

Datum: 20.06.2026



(slika je simbolična)

3-potni medenina krogelni ventil, Pneumat. vklop, T-izpust, Rp 1

Kategorija: [Brass ball valve, double-acting actuator, T-bore](#)
Šifra: **159745RIE**

Kratek opis

3-way brass ball valve, Pneumat. actuation drive, T-hole,
Operating temperature -20 °C to 70 °C, Rp 1, DN 25, PN
max. 40 bar
3-way cock, L-bore or T-bore, full bore.
Pneumatic actuators, double- or single acting version and
integrated end-position feedback.

Tehnične Specifikacije

| | |
|-----------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Adapter ventila | Supplied as standard |
| Material krogelnega ventila | Nickel-plated brass, with ISO flange plate |
| Navoj | Rp 1 |
| Pogonski material | Anodised aluminium |
| Položaj | T 3 |
| Premaz za krogelni ventil | PTFE / FKM |
| Premaz za pogon | NBR |
| Različica | double-acting |
| Max. vodeni tlak [bar] | 5.5 |
| Priporočeni vodeni tlak [bar] | 5.5 |
| Max. vodeni tlak aktuatorja [bar] | 10 |
| DN | 25 |
| D [mm] | 30.0 |
| PN [bar] | 40 |
| a/f [mm] | 41 |
| Max. delovna temperatura [°C] | 70 |
| Kot vrtenja [°] | 90 |
| L [mm] | 97.0 |
| A [mm] | 133.0 |
| B [mm] | 150.5 |