

Datum: 26.06.2026



(slika je simbolična)

3/2-5/2-potni ventil, NAMUR, G 1/4 (1), G 1/8 (3+5), 230 V, 50 Hz

Kategorija: [3/2 and 5/2-way valves NAMUR](#)
Šifra: **103647RIE**

Kratek opis

3/2-5/2-way valve, NAMUR, Anodised aluminium, Operating temp. -25 °C to 60 °C, 2 - 10 bar, G 1/4 (1), G 1/8 (3+5), 230 V, 50 Hz

Pilot-operated 3/2 and 5/2-way spool valves with threaded port connections and a NAMUR style interface. The two conversion plates supplied with each valve allow the device to be adapted to a 3/2-way or 5/2-way function.

The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-25
Električni priključek	Connector socket Pg 9P, 3 x DIN 46244 / VDE 0580
Ohišje	Aluminium, anodised black
Povezava	G 1/4 (Port 1), G 1/8 (Port 3 and 5)
Ročno upravljanje	latching
Srednje	Air, neutral gases (filtered)
Tesnilo	NBR and PUR
Diferencialni tlak min. [bar]	2
DN	6
Diferencialni tlak max. [bar]	10
Max. dovoljeni statični tlak [bar]	10
Max. delovna temperatura [°C]	60
Napetost	230 V, 50 Hz
Pretok [l/min]	700