

Datum: 04.04.2026



## 3/2-pot.vent., ročno stikalo NC bistab.G1/8 pozicije ventila 3

Kategorija: [Metalwork](#)  
Šifra: **106426RIE**

(slika je simbolična)

### Kratek opis

3/2-way valve, manual, Rotating lever, NC, bistable,  
Connection G 1/8, Operating pre. 1 - 10 bar, Operating  
temp. -10 °C to 60 °C  
3 valve positions only in conjunction with a second 3/2-way  
valve. Corresponds to a 5/3-way valve.

### Tehnične Specifikacije

|   |               |
|---|---------------|
| Min. temperaturno območje [°C]                  | -10           |
| Bat   | Aluminium     |
| Delovanje                                       | Bistable      |
| Povezava  | G 1/8         |
| Telo ventila                                    | Aluminium     |
| Tesnilo   | NBR           |
| Vzmet   | Special steel |
| Min. obratovalni tlak [bar]                     | 1             |
| Ffunkcija                                       | 3/2 NC        |
| Položaji ventilov                               | 3             |
| Max. obratovalni tlak [bar]                     | 10            |
| Simbol  | 12            |
| Max. temperaturno območje [°C]                  | 60            |
| Pretok pri 6 bar in $\Delta p$ 0,5 bar [NI/min] | 400           |
| Pretok pri 6 bar in $\Delta p$ 1,0 bar [NI/min] | 550           |