

3/2-potni el.mag. ventil ner.jeklo, NC, 24 V DC, FPM, G 1/8

Kategorija: [Solenoid valves 3/2-way type, NC, stainless steel](#)
Šifra: **158094RIE**

(slika je simbolična)

Kratek opis

3/2-way solenoid valve, Stainless steel, NC, Directly operated, 24 V DC, Medium temp. -10 °C to 100 °C, FPM, G 1/8, PN 0 - 15 bar

Tehnične Specifikacije

| | |
|------------------------------|---|
| Min. sobna temperatura [°C] | -10 |
| Min. temperatura medija [°C] | -10 |
| Električni priključek | for connector socket PG 11 P, acc. to DIN 4400 |
| Ffunkcija | normally closed (NC) |
| IP zaščita | IP 65 (with connector socket fitted) |
| Navoj | G 1/8 |
| Notranji deli | Stainless steel |
| Ohišje | Stainless steel 1.4401 |
| Sedež ventila | Stainless steel 1.4401 |
| Tesnilo | FPM |
| DN | 1.2 |
| Max. obratovalni tlak [bar] | 15 |
| Napetost | 24 V DC |
| B [mm] | 33.0 |
| Max. sobna temperatura [°C] | 60 |
| A [mm] | 60.5 |
| Max. temperatura medija [°C] | 100 |