



3/2-potni mag. ventil s kontroliranim izpustom G 3/8 NO 8

Kategorija: [Metalwork](#)
Šifra: **106870RIE**

(slika je simbolična)

Kratek opis

3/2-way solenoid valve »lineonline« controlled venting, Hose - thread, G 3/8, Hose Ø 8, NO, 24 V DC, Operating pressure 2.5-7 bar

Though small in size, these valves are solenoid-piloted and feature very high performance.

Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting.

Function corresponds to the normal position of the valve.

Tehnične Specifikacije

| | |
|--|--|
| Min. temperaturno območje [°C] | -20 |
| Ffunkcija | NO |
| Navoj | G 3/8 |
| Notranji deli | Nickel-plated brass, brass, technopolymer, stainless steel |
| Pnevmatski simboli | On housing |
| Telo | Technopolymer |
| Tesnilo | NBR |
| Vhodna moč | 1.2 W |
| Min. obratovalni tlak [bar] | 2.5 |
| Max. obratovalni tlak [bar] | 7 |
| Za cevi Ø [mm] | 8 |
| l [mm] | 18.7 |
| Operativna napetost | 24 V DC |
| Max. temperaturno območje [°C] | 60 |
| B [mm] | 63.5 |
| A [mm] | 72.4 |
| Pretok pri 6,3 bar in Δp 1,0 bar [l/min] | 700 |