

Datum: 24.06.2026



(slika je simbolična)

## 3/2-potni magnetni ventil z dušilko, G 1/4, NC, za cev 6

Kategorija: [Metalwork](#)Šifra: **106853RIE**

### Kratek opis

3/2-way solenoid valve »lineonline« silenced venting, Hose - thread, G 1/4, Hose Ø 6, NC, 24 V DC, Operating pressure 2.5 - 7 bar

Though small in size, these valves are solenoid-piloted and feature very high performance.

Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting.

Function corresponds to the normal position of the valve.

### Tehnične Specifikacije

|  |  |
|--|--|
| Min. temperaturno območje [°C]           | -20  |
| Ffunkcija                                | NC   |
| Navoj                                    | G 1/4  |
| Notranji deli                            | Nickel-plated brass, brass, technopolymer, stainless steel |
| Pnevmatski simboli                       | On housing   |
| Telo                                     | Technopolymer  |
| Tesnilo                                  | NBR  |
| Vhodna moč                               | 1.2 W  |
| Min. obratovalni tlak [bar]              | 2.5  |
| Za cevi Ø [mm]                           | 6  |
| Max. obratovalni tlak [bar]              | 7  |
| l [mm]                                   | 14.6   |
| Operativna napetost                      | 24 V DC  |
| B [mm]                                   | 57.5   |
| Max. temperaturno območje [°C]           | 60   |
| A [mm]                                   | 61.3   |
| Pretok pri 6,3 bar in Δp 1,0 bar [l/min] | 380  |