

Datum: 02.06.2026



3/2-potni mini el.magnet.ventil neposred.upravl.,NC, 24 VDC kabel

Kategorija: [Miniature solenoid valves](#)
Šifra: **106642RIE**

(slika je simbolična)

Kratek opis

3/2-way mini solenoid valve directly controlled, DN 1.5 mm, NC, 24 VDC, Cable (30 cm), Pressure 0 - 7 bar, Temp. -5 °C to 45 °C

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Material	Plastic
Ploščica na ročnem upravljalcu	Silver
Povezava	Cable (30 cm)
Srednje	Filtered, unlubricated compressed air
Tesnilo	NBR, stainless steel
Nominalni Ø [mm]	1.5
Moč tuljave [W]	2.5
Ffunkcija	3/2 NC
Max. obratovalni tlak [bar]	7
Odpiranje in zapiranje krat	10 to 12 ms (depending on pressure)
Premer [mm]	15.0
Napetost	24 V DC
Višina [mm]	42.0
Max. temperaturno območje [°C]	45