



(slika je simbolična)

3/2-potni ventil, NAMUR, monostabilen, NC, G 1/4, 230 V, 50Hz

Kategorija: [3/2-way spool valve with NAMUR style interface, NC](#)
Šifra: **103657RIE**

Kratek opis

3/2-way valve, NAMUR, NC, Anodised aluminium, Temp. max. 70 °C, Working pressure 1.5 - 10 bar, Connection G 1/4, 230 V, 50Hz

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return.

With latching manual operator and optional outgoing air restriction.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Električni priključek	Connector socket Pg 9 Plug connector PG 9, 1 coding pin, 2 Orings, 2 fixing screws
Obseg dobave	Aluminium anodised
Ohišje	G 1/4
Povezava	latching
Ročno upravljanje	Air, neutral gases (filtered)
Srednje	NBR
Tesnilo	Stainless steel
Tuljava	1.5
Min. delovni tlak [bar]	3 W=/ 5 VA~
Vhodna moč	7
DN	10
Max. delovni tlak [bar]	70
Max. delovna temperatura [°C]	230 V, 50 Hz
Napetost	1250
Pretok [l/min]	